FLAMINGO SIDE INLET TOUCH-FREE ELECTRONIC FLUSH VALVE FOR WC

SPECIFICATIONS

Touch-free electronic flush valve with a mechanical override button. Activated by infrared sensor. Shut-off valve and filter are included. Powered by a 9V battery or a 9V transformer. Battery versions include a low battery level indicator. With a 24-hour hygiene flush. Adjustable settings by remote control: sensor range, security time, delay in, delay out, on-off and reset to factory settings. Low consumption options and pre-flush operation are available upon request.

OPERATION

Touch-free electronic flush valve for W.C. Water will flush once the user moves away from the W.C.

APPLICATION

Helps washrooms stay clean and saves water. Ideal for educational institutions, gas stations, restaurants. In addition, its minimalistic style makes it perfect for any locations with high design standards.


PRODUCT AT A GLANCE				
Installation	Exposed			
Power Supply	9V Internal battery / 9V Transformer			
Hygiene flushing	Every 24 Hours for 6 seconds after the last activation			
Operating pressure	1-8.0 bar / 14.50-116 PSI			
Water flow	1.28 GPF			

OR	ORDERING INFORMATION				
PRODUCT NAME	PART NUMBER	POWER OPTIONS	ADDITIONAL SPECIFICATIONS		
FLAMINGO SIDE INLET	KSL00535	9V Internal battery / 9VTransformer	With manual override activation		

OPTIONAL ACCESSORIES				
PRODUCT NAME	PART NUMBER			
Remote Control	KSL01030			







Kassel Sanitär S.L.

• Avda. de Castilla, 1 - Polígono Industrial, 28830 San Fernando de Henares, Madrid, Spain

Daimlerstraße 2, D-93133 Burglengenfeld, Germany

Tel. +34 916 778 993 | Fax. +34 916 777 774 | info@kassel.es | www.kassel.es