SENSE, SENSOR KITS FOR URINALS

OPERATION

The urinal discharge is activated automatically when the user leaves the urinal but only after a predetermined time has passed (delay out time). The system completes one flush cycle after 6 seconds.

APPLICATION

Allows quick and easy modification of almost any traditional sanitary ware into an automatic touch-free one. It's widely utilized in environments requiring high level of hygiene, such as in hospitals, geriatric centers, prisons, restaurant kitchens and in the meat & fish industry. Being modular, it fits any interior and can be integrated with any existing water outlet. The solenoid valve is simply installed onto the water-line, allowing water to flow to the urinal.

SPECIFICATIONS

Electronic sensor kit for urinal activated by an infrared proximity sensor. Brass body with waterproof connector. Available with an IP67 battery box or a 9V transformer. Sensor range is adjustable by remote control. Other sensor settings (delay in, delay out and security time) can also be adjusted by remote control. Sensor features a low battery level indicator.

PRODUCT AT A GLANCE			
Installation	Modular		
Recommended Pressure	0.5-8.0 bar / 7.0-116 PSI With a pressure over 8 bar, use a pressure reducing valve.		
Hygiene Flush	To maximize hygiene, this product is equipped with a 24 hours duty flush. The flush takes place after 24 hours of non use have passed. Prevents the trap seal from drying out, possible freezing of pipes, and gets rid of potential bacteria in stuck water. This function can be disabled using the remote control.		


POWER SUPPLY OPTIONS



ORDERING INFORMAT	ION	OPTIONAL ACCESSORIES	
PRODUCT NAME	PART NUMBER	PRODUCT NAME	PART NUMBER
SENSE, SENSOR KIT FOR URINAL	KSL00460		
SENSE, SENSOR KIT FOR URINAL FRONT FIXATION	KSL00470	REMOTE CONTROL	KSL01030









Kassel Sanitär S.L.

- Avda. de Castilla, 1 Polígono Industrial, 28830 San Fernando de Henares, Madrid, Spain Daimlerstraße 2, D-93133 Burglengenfeld, Germany